

ACTIVE SENSOR SRD2PB



E-number	13 020 37
Art. number	V-44B0306-035Y
Designation	SRD2PB
Model series	V-sense
Voltage in	220-240VAC
Frequency in	50Hz, 60Hz
Radio frequencies	2402MHz-2480MHz
Maximum radio frequency effect	8dBm
Standby effect	<0,5W
Lux range	1-999lux
Number of push-button inputs	2
Maximum DALI output	40mA (20 DALI-drivers)
Maximum breaking capacity relay output	10A (cos φ =1)
Maximum inrush current relay output	200A / 300 μ s
Maximum load relay output	Incandescent/halogen: 10A LED-loads: 2,5A Fluorescent, uncompensated: 6,25A Fluorescent, compensated: 5A Low voltage halogen, electronic: 5A Low voltage halogen, conventional: 3A Energy-saving lamps: 2,5A Motors and fans: 2,5A
Memorizes last set position	Yes
Overheating protection	Yes
Mounting	Recessed (surface mounting achieved with accessories sold separately)
Working air humidity	0...80%, non-condensing
Working temperature	-20 to +35°C
Dimensions (BxH)	90x81mm
Weight	124g
Cable area	2,5mm ²
Cable outer diameter	7mm-13mm
Housing material	PC/ABS
Insulation class	IP20
Enclosure class	II
Approvals	CE, UKCA

